



**NEW &
IMPROVED**

PK2X

Pocket Stroboscope

- Internal rechargeable Lithium Ion battery uses the latest "smart-charge" technology for the longest possible life and 2-hour run-time on a single charge.
- Can be powered directly from an AC power source for continuous operation, or continued use during recharging.
- Includes Traceable Calibration Certificate.
- Resolution of ± 1 RPM over the entire range with precise flash control and drift-free operation.
- Bright XENON flash intensity (over 1200 Lux) with life of 200 million flashes.
- Accepts input from sensors for external flash triggering.
- Provided with a threaded insert for mounting to articulating arm or other fixture.
- Universal AC-Adapter/Charger (100 – 240V AC) with plug adapters provided for use in North America, Europe, United Kingdom and Australia.

The new PK2X hand-held Pocket Strobe® easily measures RPM of rotating or reciprocating parts without contact. It allows moving parts/machinery inspection by "freezing" or "slowing down" the action using the stroboscopic effect. The PK2X's small size, lightweight design and rugged construction make it perfect for field technicians or maintenance personnel.

The PK2X offers the highest reliability, refined by more than 10-years of continuous design and manufacturing improvements since the original PK1 hand-held Pocket Strobe was introduced in 1996.

The PK2X provides one hand operation, yet delivers performance comparable to much larger and heavier pistol-grip type models. It is an ideal choice for industrial, laboratory, R&D and academic environments.



The new PK2X offers significant improvements over the previous generation model PK2 including:

- 50% increase in **BRIGHTNESS**.
- 200% increase in **BATTERY LIFE** (2 hours).
- Now operates from either **AC POWER** or internal **BATTERY**.

The PK2X's small size and excellent performance provide superior convenience and value—at a reasonable price.

Specifications

Flash Range	30 – 12,500 FPM
Flash Brightness	1200 Lux (8"/20cm distance @ 4500 fpm)
Accuracy	$\pm 0.01\%$ over entire range +1 LSD ± 0.04 Hz
Resolution	± 1 FPM over entire range
Display	5-digit LCD
Display Update	0.5 seconds
Flash Energy	170 mJ
Flash Duration	< 9 μ s
Flash Tube Life	200 million flashes (at 6,000 fpm)
Flash Color Temp	6,000K – 6500K
External Trigger	0-5 volt, DTL/TTL compatible 1/8" jack
Optional Trigger Signal Output (PK2X-OT Only)	0-5 volt, DTL/TTL compatible 1/8" jack
Operating Time	Battery, 2 hours AC-Power, continuous

Battery Type	Lithium Ion (Li-Ion)
Battery Charger	AC Power Required, 100-240 VAC, 50/60 Hz DC-Output, 9 VDC @ 2000 mA max Charging Time, 4-5 hours
Overcharge Protection	Yes
CE Certification	Yes
Weight	0.9 lbs (415 grams) including battery
Housing Material	High Impact ABS Plastic
Reflector Material	Aluminum
Tripod Mount	1/4-20, female insert
Operating Temp.	32 to 104° F (0 to 40° C)
Dimensions	9-3/4" x 2-3/4" x 1-3/4" (240 x 65 x 40 mm)
Warranty	1 year

Stroboscopic Effect



The stroboscopic effect is accomplished by matching the flash rate of the strobe with the repetitive rate (RPM) of motion of the target. If the flash rate and RPM match the object will appear motionless. A slight mismatch of the relative speeds will create a slow motion effect.

Complete Kit

Includes: Stroboscope, Universal AC Adapter/Charger (with plug adapters for North America, Europe, United Kingdom and Australia), external input/output jack, Traceable Calibration Certificate and instruction manual, all supplied in a hard-shell carrying case.



Available Models

- PK2X** Includes Strobe, Universal AC-adapter/charger and external trigger jack in carrying case with Traceable Calibration Certificate.
- PK2X-OT** Same as above with optional trigger output signal.
- PK2X-AC** Includes Strobe *without battery* for operation on AC power ONLY. Includes universal AC-adapter, external trigger jack in carrying case with Traceable Calibration Certificate.

CHECK•LINE® – PRECISION QUALITY CONTROL INSTRUMENTS

Electromatic Equipment Co., Inc.
600 Oakland Ave.
Cedarhurst, N Y 11516 —USA

Tel: (800) 645-4330 (USA & Canada)
Tel: (516) 295-4300
Fax: (516) 295-4399

Email: info@checkline.com
Website: www.checkline.com

FOR ADDITIONAL INFORMATION OR TO PLACE AN ORDER CALL TOLL FREE 1-800-645-4330