

3-Channel TENSION INDICATOR

SC Series

SC-1-N (1 Channel)

SC-2-N (2 Channel)

SC-3-N (3 Channel)

The new SC Series Tension Indicators permit the user to connect from one to three THR 3-Roller Tension Sensors. The SC Indicators provide a regulated DC power source for the sensors and includes a 3-1/2 Digit LED tension display, calibration adjustment pots and 0–10 VDC analog outputs.

FEATURES

- Supplies separate 0–10 VDC analog output for each channel
- Adjustable output frequency of 1.6/3.3/15/330 Hz.
- Front panel calibration adjustment pots for each channel
- Includes wall-mount bracket
- Includes AC-Adapter, 115 VAC (for 230 VAC, add “-220” suffix)



Model SC-2-N

Model SC-3-N



Model SC-1

Specifications

Display Ranges	0–50.0, 0–100.0, 0–199.9, 0–500, 0–1000, 0–1999, 0–2.00, 0–5.00, 0–10.00 and 0–19.99, switch selectable
Units of Measure	grams, cN or volts
Power for Sensors	+12 V DC
Analog Output	0–10 V DC, proportional to tension
Frequency Response	1.6, 3.3, 15 or 330 Hz, selectable
Enclosure	Extruded Aluminum
Dimensions	7.5 x 4.2 x 1.3" (190 x 106 x 34mm)
Power Required	9–15 V DC or 9–15 V AC (supplied with AC-Adapter)
Operating Temp.	32 to 120 °F (0 to 45 °C)
Accessories Included	AC Adapter, Mounting bracket, output plugs (3) and instruction manual

Visit us on the World Wide Web at www.checkline.com

ELECTROMATIC Equipment Co., Inc., 600 Oakland Ave., Cedarhurst, NY 11516 – USA
Tel: 800-645-4330 (USA & Canada) ■ Tel: (516) 295-4300 ■ Fax: (516) 295-4399