

MTWD-S

Digital Torque Wrench

Features

- Accuracy +/- 2.5% of reading CW, +/- 1 digit
Accuracy +/- 3% of reading CCW , +/- 1 digit
- Designed for daily screw tightening production environment.
- Program pre-set torque.
- Visual, acoustic and sensory signal (handle vibrates) when the set torque is reached.
- Four units of torque measurement available: N.m, lbf.ft, lbf.in, kgf.m
- Heavy duty bi-directional ratchet head.
- Operating mode: Peak
- Holds "Peak" torque readings for 15 seconds.
- Large LCD screen for high visibility.
- Lightly knurled non-slip grip.
- Four-digit display.
- Battery operation.



Model	Item #	lbf.in	Torque Ranges		N.m	Square Drive	Length		Weight	
			lbf.ft				in.	mm	lbs.	kg.
MTWD135-S	290131	132.8-1195	11.1-99.6		15-135	3/8"	15 1/2"	394	2.4	1.1
MTWD135-S	290132	132.8-1195	11.1-99.6		15-135	1/2"	15 1/2"	394	2.4	1.1
MTWD200-S	290133	221.3-1780	18.5-147		25-200	3/8"	22 3/8"	569	3	1.4
MTWD200-S	290134	221.3-1780	18.5-147		25-200	1/2"	22 3/8"	569	3	1.4
MTWD340-S	290135	345.2-3010	28.8-250		39-340	1/2"	30 1/4"	769	3.7	1.7

 **Note!** Uses standard AAA batteries